



Main

Range	Linery
Product name	Linery DS
Product or component type	Distribution block

Complementary

Mounting support	DIN rail
Range compatibility	Prisma G Prisma P Prisma PH Prisma Pack Spacial Kaedra Pragma TeSys
Product compatibility	Spacial enclosures
Poles description	4P
Distribution block outgoers	4 x 12 holes
[Ue] rated operational voltage	230 V AC Ph/N 440 V AC Ph/Ph
[Ui] rated insulation voltage	500 V AC
[Uimp] rated impulse withstand voltage	8 kV
[Ie] rated operational current	160 A at 40 °C
[Icw] rated short-time withstand current	8.4 kA for 1 s
[Ipk] rated peak withstand current	36 kA
Connections - terminals	Distribution: screw terminal 8 cable(s) 2.5...25 mm ² rigid Distribution: screw terminal 8 cable(s) 1.5...16 mm ² flexible with cable end Distribution: screw terminal 3 cable(s) 4...25 mm ² flexible with cable end Supply: screw terminal 1 cable(s) 25...70 mm ² rigid Supply: screw terminal 1 cable(s) 16...50 mm ² flexible with cable end Distribution: screw terminal 3 cable(s) 10...35 mm ² rigid
Tightening torque	Distribution: 2 N.m flat screwdriver 7.5 mm Distribution: 2 N.m PZ2 screwdriver 7.5 mm Supply: 5 N.m flat screwdriver 12 mm Supply: 5 N.m PZ2 screwdriver 12 mm Distribution: 2.5 N.m flat screwdriver 9 mm Distribution: 2.5 N.m PZ2 screwdriver 9 mm

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

9 mm pitches	18
Height	100 mm
Width	162 mm
Depth	50.5 mm
Net weight	0.557 kg
Colour	White (RAL 9003)

Environment

Pollution degree	3
Overvoltage category	III
Dielectric strength	2500 V
Standards	EN/IEC 61439-1 EN/IEC 60947-7-1
Ambient air temperature for operation	-25...55 °C

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	620 g
Package 1 Height	5.7 cm
Package 1 width	10.7 cm
Package 1 Length	17.8 cm
Unit Type of Package 2	S03
Number of Units in Package 2	25
Package 2 Weight	16.034 kg
Package 2 Height	30 cm
Package 2 width	30 cm
Package 2 Length	40 cm

Offer Sustainability

EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Contractual warranty

Warranty	18 months
----------	-----------