


Product datasheet

Specifications



IP30 transparent door, W = 400 mm

08534

⚠ Discontinued on: 15 Jun 2023

⚠ To be end-of-service on: 30 Apr 2025

⚠ Discontinued - Service only

Main

| | |
|---------------------------|---|
| Range | Prisma |
| Range Of Product | Prisma P |
| Product Or Component Type | Door |
| Range Compatibility | Prisma Prisma P cubicle duct |
| Provided Equipment | door handle keylock (key 405) other keylock and insert to be ordered separately 2 hinge |
| Enclosure Mounting | Floor-standing |
| Type Of Door | Transparent |
| Ip Degree Of Protection | IP30 |

Complementary

| | |
|------------------------------------|------------------------------|
| Installation Description | Cubicle duct - width 400 mm |
| Door Opening Side | Reversible |
| Number Of Locks | 2 |
| Door Opening Angle | 120 ° |
| Number Of Vertical Modules [50 Mm] | 36 |
| Enclosure Material | Glass Treated sheet steel |
| Quantity Per Set | Set of 1 |
| Height | 2000 mm |
| Width | 400 mm |
| Depth | 30 mm |
| Net Weight | 12 kg |
| Surface Finish | Smooth Matt |
| Colour | White (RAL 9001) |

Environment

| | |
|-------------------------|---------------------------------|
| Ik Degree Of Protection | IK08 conforming to EN/IEC 62262 |
| Standards | IEC 61439-1 IEC 61439-2 |

| | |
|-----------------------------|--|
| Protective Treatment | Electrophoresis treatment and hot-polymerised polyester epoxy powder |
|-----------------------------|--|

Packing Units

| | |
|-------------------------------|-----|
| Unit Type Of Package 1 | PCE |
|-------------------------------|-----|

| | |
|-------------------------------------|---|
| Number Of Units In Package 1 | 1 |
|-------------------------------------|---|

| | |
|-------------------------|----------|
| Package 1 Height | 8.000 cm |
|-------------------------|----------|

| | |
|------------------------|-----------|
| Package 1 Width | 41.000 cm |
|------------------------|-----------|

| | |
|-------------------------|------------|
| Package 1 Length | 203.000 cm |
|-------------------------|------------|

| | |
|-------------------------|-----------|
| Package 1 Weight | 12.000 kg |
|-------------------------|-----------|

| | |
|-------------------------------|-----|
| Unit Type Of Package 2 | P2M |
|-------------------------------|-----|

| | |
|-------------------------------------|----|
| Number Of Units In Package 2 | 20 |
|-------------------------------------|----|

| | |
|-------------------------|-----------|
| Package 2 Height | 95.000 cm |
|-------------------------|-----------|

| | |
|------------------------|------------|
| Package 2 Width | 200.000 cm |
|------------------------|------------|

| | |
|-------------------------|------------|
| Package 2 Length | 120.000 cm |
|-------------------------|------------|

| | |
|-------------------------|------------|
| Package 2 Weight | 240.000 kg |
|-------------------------|------------|

Contractual warranty

| | |
|-----------------|-----------|
| Warranty | 12 months |
|-----------------|-----------|

Sustainability

Green Premium™ label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)



Transparency RoHS/REACH

Well-being performance

Mercury Free

RoHS Exemption Information Yes

Certifications & Standards

Eu RoHS Directive Pro-active compliance (Product out of EU RoHS legal scope)
[EU RoHS Declaration](#)

China RoHS Regulation [China RoHS declaration](#)
Product out of China RoHS scope. Substance declaration for your information

Environmental Disclosure [Product Environmental Profile](#)

Circularity Profile [End of Life Information](#)