

AUXIL. SWITCH, TRANSVERSE, 1 C, FOR CIRCUIT-BREAKERS, SIZES00



Figure similar

General technical data:		
product brand name		SIRIUS
Product designation		auxiliary switch, transverse on the front
Design of the product		transverse auxiliary switches
Size of the circuit-breaker		S00, S0, S2, S3
Protection class IP on the front		IP20
Ambient temperature		
• during storage	°C	-50 ... +80
• during operation	°C	-20 ... +60

Auxiliary circuit:		
Number of NC contacts for auxiliary contacts instantaneous contact		0
Number of NO contacts for auxiliary contacts instantaneous contact		0
Number of CO contacts of the auxiliary contacts instantaneous contact		1
Operating current		
• of the auxiliary contacts		
— at AC-12		

— at 24 V	A	10
— at 230 V	A	10
— at 400 V	A	10
— at 690 V	A	10
— maximum	A	10
— at AC-15		
— at 24 V	A	4
— at 230 V	A	3
— at 400 V	A	1.5
— at DC-13		
— at 24 V	A	1
— at 110 V	A	0.22
— at 220 V	A	0.1
• at AC-15 at 690 V Rated value	A	0.5

#### Installation/ mounting/ dimensions:






<b>Mounting type</b>		plug-in fixing
<b>Width</b>	mm	45
<b>Height</b>	mm	12
<b>Depth</b>	mm	17





#### Connections/ Terminals:


Type of electrical connection for auxiliary and control current circuit		screw-type terminals
<b>Type of connectable conductor cross-section</b>		
• for auxiliary contacts		
— solid		2x (0.5 ... 1.5 mm <sup>2</sup> ), 2x (0.75 ... 2.5 mm <sup>2</sup> )
— finely stranded		
— with core end processing		2x (0.5 ... 1.5 mm <sup>2</sup> ), 2x (0.75 ... 2.5 mm <sup>2</sup> )
• for AWG conductors for auxiliary contacts		2x (18 ... 14)

#### Certificates/ approvals:

<b>Certificate of suitability</b>		CE / UL / CSA / CCC
-----------------------------------	--	---------------------

General Product Approval			Declaration of Conformity	Test Certificates	Shipping Approval
 CCC	 CSA	 UL	 EG-Konf.	<a href="#">spezielle Prüfbescheinigungen</a> <u>n</u>	 BUREAU VERITAS

Shipping Approval				other	
 DNV	 GL	 LRS	 RMRS	<a href="#">Umweltbestätigung</a>	<a href="#">Bestätigungen</a>

other
 VDE

#### Further information

**Information- and Downloadcenter (Catalogs, Brochures,...)**

<http://www.siemens.com/industrial-controls/catalogs>

**Industry Mall (Online ordering system)**

<http://www.siemens.com/industrymall>

**Cax online generator**

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3RV19011D>

**Service&Support (Manuals, Certificates, Characteristics, FAQs,...)**

<https://support.industry.siemens.com/cs/ww/en/ps/3RV19011D>

**Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)**

[http://www.automation.siemens.com/bilddb/cax\\_de.aspx?mlfb=3RV19011D&lang=en](http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3RV19011D&lang=en)

last modified:

20.07.2015