

Product details page



RTX³ LEGRAND

RCCB RX3 4P 25A 30MA AC

REF. 402062 | EAN. 3245064020626

> [The product details page](#)

Caractéristiques techniques

| | |
|---------------------------------------|----------|
| Number of poles | 4 |
| Rated voltage | 400 V |
| Rated current | 25 A |
| Rated fault current | 0.03 A |
| Rated insulation voltage Ui | 500 V |
| Rated impulse withstand voltage Uimp | 4 kV |
| Mounting method | DIN rail |
| Leakage current type | AC |
| Selective protection | No |
| Short-time delayed tripping | No |
| Short-circuit breaking capacity (Icw) | 10 kA |
| Surge current capacity | 0.25 kA |
| Voltage type | AC |
| With interlocking device | Yes |
| Frequency | 50 Hz |
| Additional equipment possible | No |
| Degree of protection (IP) | IP20 |
| Width in number of modular spacings | 4 |
| Built-in depth | 44 mm |

| | |
|---|-------------------------------------|
| Ambient temperature during operating | -25-60 °C |
| Pollution degree | 2 |
| Connectable conductor cross section multi-wired | 0.75-35 mm ² |
| Connectable conductor cross section solid-core | 0.75-50 mm ² |
| RAL-number (similar) | 7035 |
| Explosion-proof | No |
| Width | 71.2 mm |
| Height | 88.9 mm |
| Depth | 78.85 mm |
| Degree of impact strength (IK) | IK04 |
| Storage temperature | -40-70 °C |
| Nominal voltage | 340-440 V |
| Electric supplying direction | By the top or bottom |
| Terminal marking indication | Yes |
| Stress test conformity (1000V) | Yes |
| Colour | Grey |
| Halogen free | Yes |
| Connection type | Screwed terminal , Busbar and cable |

Label space/information surface

No

Documentation

Documentation technique

 F01536EN-02.pdf | PDF (0.96Mo)

Certificats et agréments

 VDE-40034493 | (0.38Mo)

 LGRP-00366-V02.01-EN.pdf | PDF (0.64Mo)

 LGRP-00366-V02.01-FR.pdf | PDF (0.6Mo)

 OC / CB-CB FR_705078/M1 | (3.33Mo)

Objet BIM & logiciel métier

 402076.dwg | DWG (0.13Mo)