

Product details page



RTX³ LEGRAND

RCCB RX3 4P 40A 30MA AC

REF. 402063 | EAN. 3245064020633

> [The product details page](#)

Caractéristiques techniques

Number of poles	4
Rated voltage	400 V
Rated current	40 A
Rated fault current	0.03 A
Rated insulation voltage Ui	500 V
Rated impulse withstand voltage Uimp	4 kV
Mounting method	DIN rail
Leakage current type	AC
Selective protection	No
Short-time delayed tripping	No
Short-circuit breaking capacity (Icw)	10 kA
Surge current capacity	0.25 kA
Voltage type	AC
With interlocking device	Yes
Frequency	50 Hz
Additional equipment possible	No
Degree of protection (IP)	IP20
Width in number of modular spacings	4
Built-in depth	44 mm

Ambient temperature during operating	-25-60 °C
Pollution degree	2
Connectable conductor cross section multi-wired	0.75-35 mm ²
Connectable conductor cross section solid-core	0.75-50 mm ²
RAL-number (similar)	7035
Explosion-proof	No
Width	71.2 mm
Height	88.9 mm
Depth	78.85 mm
Degree of impact strength (IK)	IK04
Storage temperature	-40-70 °C
Nominal voltage	340-440 V
Electric supplying direction	By the top or bottom
Terminal marking indication	Yes
Stress test conformity (1000V)	Yes
Colour	Grey
Halogen free	Yes
Connection type	Screwed terminal , Busbar and cable

Label space/information surface

No

Documentation

Documentation technique

 F01536EN-02.pdf | PDF (0.96Mo)

Certificats et agréments

 VDE-40034493 | (0.38Mo)

 LGRP-00366-V02.01-EN.pdf | PDF (0.64Mo)

 LGRP-00366-V02.01-FR.pdf | PDF (0.6Mo)

 OC / CB-CB FR_705078/M1 | (3.33Mo)

Objet BIM & logiciel métier

 402076.dwg | DWG (0.13Mo)