

Product details page



LEGRAND

RCCB RX3 4P 63A AC 30MA

REF. 402064 | EAN. 3245064020640

[> The product details page](#)

Caractéristiques techniques

Number of poles	4
Rated voltage	400 V
Rated current	63 A
Rated fault current	0.03 A
Rated insulation voltage U_i	500 V
Rated impulse withstand voltage U_{imp}	4 kV
Mounting method	DIN rail
Leakage current type	AC
Selective protection	No
Short-time delayed tripping	No
Short-circuit breaking capacity (I_{cw})	10 kA
Surge current capacity	0.25 kA
Voltage type	AC
With interlocking device	Yes
Frequency	50 Hz
Additional equipment possible	No
Degree of protection (IP)	IP20
Width in number of modular spacings	4
Built-in depth	44 mm

Ambient temperature during operating	-25-60 °C
Pollution degree	2
Connectable conductor cross section multi-wired	0.75-35 mm ²
Connectable conductor cross section solid-core	0.75-50 mm ²
RAL-number (similar)	7035
Explosion-proof	No
Width	71.2 mm
Height	88.9 mm
Depth	78.85 mm
Degree of impact strength (IK)	IK04
Storage temperature	-40-70 °C
Nominal voltage	340-440 V
Electric supplying direction	By the top or bottom
Terminal marking indication	Yes
Stress test conformity (1000V)	Yes
Colour	Grey
Halogen free	Yes
Connection type	Screwed terminal , Busbar and cable

Label space/information surface

No

Documentation

Documentation technique

 F01536EN-02.pdf | PDF (0.96Mo)

Certificats et agréments

 VDE-40034493 | (0.38Mo)

 LGRP-00366-V02.01-EN.pdf | PDF (0.64Mo)

 LGRP-00366-V02.01-FR.pdf | PDF (0.6Mo)

 OC / CB-CB FR_705078/M1 | (3.33Mo)

Objet BIM & logiciel métier

 402076.dwg | DWG (0.13Mo)