

Product details page



RTX³ LEGRAND

RX3 DISJ 1P+N G C25 4500A 1 MOD

REF. 419951 | EAN. 3414970693990

> [The product details page](#)

Caractéristiques techniques

Built-in depth	44 mm
Release characteristic	C
Number of poles (total)	2
Number of protected poles	1
Rated current	25 A
Rated voltage	230 V
Rated insulation voltage Ui	250 V
Rated impulse withstand voltage Uimp	4 kV
Rated short-circuit breaking capacity Icn according to EN 60898 at 230 V	4.5 kA
Voltage type	AC
Frequency	50-60 Hz
Current limiting class	3
Flush-mounted installation	Yes
Concurrently switching neutral conductor	Yes
Pollution degree	2
Additional equipment possible	Yes
Width in number of modular spacings	2

Degree of protection (IP)	IP20
Explosion-proof	No
Width	17.8 mm
Height	88.7 mm
Depth	77.5 mm
Degree of impact strength (IK)	IK04
Storage temperature	-40-70 °C
Nominal voltage	210-250 V
Electric supplying direction	By the top or bottom
Terminal marking indication	Yes
Colour	Grey
RAL-number	7035
Halogen free	Yes
Connection type	Screwed terminal , Busbar and cable
Label space/information surface	No
Mounting method	DIN rail

Documentation

Documentation technique

 F02068EN-00.pdf | PDF (0.62Mo)

 F02068FR-00.pdf | PDF (0.61Mo)

Certificats et agréments

 OC / CB-FR_716633 | (0.68Mo)

 LGRP-00358-V02.01-EN.pdf | PDF (0.65Mo)

 LGRP-00358-V02.01-FR.pdf | PDF (0.62Mo)

 VDE-40042981 | (0.74Mo)

Objet BIM & logiciel métier

 419694.dwg | DWG (0.18Mo)