

Product sheet



- LEGRAND

Complete ONE FAMILY kit with colour 7" video indoor unit with handset and Entrance Panel, with rain-shield.

REF. 369570 | EAN. 3414970829573

> [Visit e-catalogue](#)

Product characteristics

- Expandable up to 4 additional Internal Units and up to 1 additional External Panel or an External Camera (NTSC or PAL)
- Offering the following functions : call, intercom, door lock activation, image cycling
- Wall mounted with internal power supply

Les + prod

Installation

- 4-wires cabling

With video	Yes
Number of indoor stations	4
Number of outdoor stations	4
Installation technique	Multi-wire system
Mounting method indoor station	Flush-mounted
Colour indoor station	White
Mounting method outdoor station	Other
Material outdoor station	Other
Colour outdoor station	Silver
Expandable to max. number of indoor stations	0
Expandable to max. number of outdoor stations	0
Picture system	PAL
Can be connected to smartphone	No
Internal communication	Yes
Hands free	No
With day/night function	No

Voltage type	AC
Nominal voltage	12-24 V
Supply current	1-1 A
Frequency	50-60 Hz
Sound level	82 dB
Standby consumption	10 mA
Halogen free	No
Antimicrobial treatment	No
Cable nature for connection	Flexible or rigid
Cable section	0.28-1.5 mm ²
Fitted with USB plug	No
Fitted with rainproof plate protection	Yes
With complementary luminous signal	Yes
Mounting method	Other
Vertical fixing center distance	1600-1650 mm
Horizontal fixing center distance	50-100 mm

Opening angle camera	80 °	Control mode	Wired
Zoom, pan/tilt function	No	Contains Batteries and/or Accumulator	No
With memory function	No	Additional unit	Yes
Manual adjustable camera	Yes	Loudness setting	Yes
Label space/information surface	Yes	Addressable	No
Hearing aid compatible	No	Door entry system with mobile application	No
Compatible with Apple HomeKit	No	Number of ringtones	12
Compatible with Google Assistant	No	Remote opening of gate / Electric door opener	No
Compatible with Amazon Alexa	No	Screen resolution	852x480
IFTTT support available	No	Screen brightness setting	Yes
Width	54 mm	Screen contrast setting	Yes
Height	119 mm	Memory video function	No
Depth	40 mm	Camera type	Fixed
Degree of impact strength (IK)	IK07	Max distance between internal and external unit	100 m
Degree of protection (IP)	IP54	Communication rank type	Other
Operating / setting temperature	-15-50 °C	Connected object	No
Storage temperature	-10-70 °C		

Documentation

TECHNICAL DOCUMENTATION

 LE09362AA.pdf | PDF (9.14Mo)

CATALOGUE PAGE & OTHERS

 ex223001_0850.pdf | PDF (0.1Mo)