

# Product sheet



- LEGRAND

Complete ONE FAMILY kit with colour 7" video indoor unit hands-free and Entrance Panel, with rain-shield. 4 wires

REF. 369580 | EAN. 3414970829610

> [Visit e-catalogue](#)

## Product characteristics

- Expandable up to 4 additional Internal Units and up to 1 additional External Panel or an External Camera (NTSC or PAL)
- Offering the following functions : call, intercom, door lock activation, image cycling
- Wall mounted with internal power supply

## Les + prod

### Installation

- 4-wires cabling

With video	Yes
Number of indoor stations	4
Number of outdoor stations	4
Installation technique	Multi-wire system
Mounting method indoor station	Flush-mounted
Colour indoor station	White
Colour outdoor station	Silver
Hands free	Yes
Opening angle camera	80 °
With memory function	No
Label space/information surface	Yes
Compatible with Apple HomeKit	No
Compatible with Google Assistant	No
Compatible with Amazon Alexa	No
IFTTT support available	No
Width	54 mm

Supply current	1-1 A
Frequency	50-60 Hz
Halogen free	No
Antimicrobial treatment	No
Cable nature for connection	Flexible or rigid
Fitted with USB plug	No
Fitted with rainproof plate protection	Yes
With complementary luminous signal	Yes
Vertical fixing center distance	1600-1650 mm
Horizontal fixing center distance	500-500 mm
Control mode	Wired
Contains Batteries and/or Accumulator	No
Additional unit	Yes
Loudness setting	Yes
Addressable	No
Door entry system with mobile application	No

Height	119 mm	Number of ringtones	12
Depth	40 mm	Remote opening of gate / Electric door opener	No
Degree of impact strength (IK)	IK07	Screen resolution	852x480
Degree of protection (IP)	IP54	Screen brightness setting	Yes
Operating / setting temperature	-15-50 °C	Screen contrast setting	Yes
Storage temperature	-10-70 °C	Camera type	Fixed
Voltage type	AC	Max distance between internal and external unit	100 m
Nominal voltage	12-24 V	Connected object	No

## Documentation

---

### TECHNICAL DOCUMENTATION

 LE09360AA.pdf | PDF (10.58Mo)

### CATALOGUE PAGE & OTHERS

 ex223001\_0850.pdf | PDF (0.1Mo)