

ECS8060



SLOTTED TRUNKING WITH COVER S 4/6/4 DIM. 80X60

Goulottes > Systèmes de tableaux de distribution > Systèmes de câblage > Goulottes > Goulotte de câblage > Gris - type s - lamelles Étroites 4/6/4




IMMAGINE
RAPPRESENTATIVA



REPRESENTATIVE
IMAGE

Symboles/marques/approbations techniques



Normes

EN 50085-1 EN 50085-2-3 UL 1565

Description

Slotted trunking made of self-extinguishing PVC-based technopolymer (UL94 - V0). Perforated bottom according to the Standard DIN 43659. Second break line at the base of the slots permits to remove the whole trunking wall (with tool).

Etim

GROUP EG000007 - Goulottes de câblage

CLASS EC000012 - Goulotte de câblage

Matériau	PVC	Sans halogène	No	Couleur	Gris
Type de fixation	Perforation du fond	Largeur	80 mm	Hauteur	60 mm
Longueur	2 m	Distance entre les fentes	6 mm	Largeur de fente	4 mm
Finition de paroi latérale	Poinçonnage à trous/fentes	Auto-extinguible	Oui	Flexible	No
Section transversale utile	4202 mm²	Avec partie supérieure	Oui	Numéro RAL	7030

Caractéristiques techniques

Prédisposition du séparateur SI (2)

Documentation disponible en téléchargement



Certification

Certificato UL A-S
ATL AMF
E331386.pdf



Certification

RINA
DCMTVL_1005538
_380865962_2025.
PDF



Certification

Canali asolati tipo S
IMQ_EI617_2020.p
df

Code à barres



8054320286356

Cardboard

28 MT

0.26x0.18x2.027 [m]

21.5012 [kg]



8054320280651

Pallet

504 MT

387.0216 [kg]